

# MATERIAL SAFETY DATA SHEET

## SECTION 1

## PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT

**Product Name:** Hisheng microcrystalline wax

**Grade :** MW70 /MW80

**CAS NO :**63231-60-7

**Intended Use:** Pigment Dispersion, Hot melt adhesive, Road Marking Paint, Color Master batch

### COMPANY IDENTIFICATION

**Supplier:** Qingdao Hongsheng New Material Co.,ltd

**Transportation Emergency Phone** 0086-18562651969

## SECTION 2

## COMPOSITION / INFORMATION ON INGREDIENTS

**No Reportable Hazardous Substance(s) or Complex Substance(s).**

**NOTE:** The product may contain varying levels of additives such as slip and antiblocking agents, antioxidants and stabilizers.

## SECTION 3

## HAZARDS IDENTIFICATION

This material is not considered to be hazardous according to regulatory guidelines (see (M)SDS Section 15).

### POTENTIAL PHYSICAL / CHEMICAL EFFECTS

High dust levels may create potential for explosion. Spilled pellets present a slipping hazard on hard surfaces. Contact with hot material can cause thermal burns which may result in permanent damage or blindness. Material can accumulate static charges which may cause an incendiary electrical discharge.

### POTENTIAL HEALTH EFFECTS

Material is essentially non-toxic. However, if dust is generated, it could scratch the eyes and cause minor irritation to the respiratory tract. When heated, the vapors/fumes given off may cause respiratory tract irritation.

**NFPA Hazard ID:** Health: 1 Flammability: 1 Reactivity: 0

**HMIS Hazard ID:** Health: 1 Flammability: 1 Reactivity: 0

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

## SECTION 4

## FIRST AID MEASURES

### INHALATION

In case of adverse exposure to vapors and / or aerosols formed at elevated temperatures, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest.

**SKIN CONTACT**

Wash contact areas with soap and water. For hot product: Immediately immerse in or flush affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention.

**EYE CONTACT**

Flush thoroughly with water. If irritation occurs, get medical assistance.

**INGESTION**

First aid is normally not required. Seek medical attention if discomfort occurs.

**SECTION 5****FIRE FIGHTING MEASURES****EXTINGUISHING MEDIA**

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight Streams of Water

**FIRE FIGHTING**

**Fire Fighting Instructions:** Assure an extended cooling down period to prevent re-ignition. Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Unusual Fire Hazards:** High dust levels may create potential for explosion.

**SECTION 6****ACCIDENTAL RELEASE MEASURES****NOTIFICATION PROCEDURES**

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**SPILL MANAGEMENT**

**Land Spill:** Spilled pellets present a slipping hazard on hard surfaces. Small Dry Spills: With clean shovel place material into clean, dry container and cover loosely; move containers from spill area.

**Water Spill:** Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Skim from surface.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

**ENVIRONMENTAL PRECAUTIONS**

Prevent entry into waterways, sewers, basements or confined areas.

person-related safety precautions:

particular danger of slipping on leaked/ spilled product  
see point 8

measures for environmental protection:  
no special measures required

---

measures for cleaning / collecting:  
recycle product or dispose properly

## SECTION 7 HANDLING AND STORAGE

### HANDLING

Avoid conditions which create dust. Avoid elevated temperatures for prolonged periods of time. Prevent small spills and leakage to avoid slip hazard. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Material can accumulate static charges which may cause an electrical spark (ignition source). Care should be taken when storing and handling this product. Apart from the specific nature of the polymer product, conditions such as humidity, sunlight, and temperature have an influence on the way the product behaves during storage and handling. Special attention should be paid to avoid inappropriate stacking of palletized bags or other package units. Avoid conditions generating heat during transfer operations.

**Loading/Unloading Temperature:** [Ambient ]

**Transport Temperature:** [Ambient ]

**Transport Pressure:** [Ambient ]

### STORAGE

Store in a cool, dry place with adequate ventilation. Keep away from incompatible materials, open flames, and high temperatures. Do not store in open or unlabelled containers.

**Storage Temperature:** [Ambient ]

**Storage Pressure:** [Ambient ]

**Suitable Containers/Packing:** Bags

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure limits/standards for materials that can be formed when handling this product:** For dusty conditions, OSHA recommends for particulates not otherwise regulated an 8-hour TWA of 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction); ACGIH recommends for insoluble and poorly soluble particles not otherwise specified an 8-hour TWA of 10 mg/m<sup>3</sup> (inhalable particles), 3 mg/m<sup>3</sup> (respirable particles).

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

### ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Adequate ventilation should be provided so that exposure limits are not exceeded. **SPECIAL PRECAUTIONS:** Should significant vapors/fumes be generated during thermal processing of this product, it is recommended that work stations be monitored for the presence of thermal degradation by-products which may evolve at elevated temperatures (for example, oxygenated components). Processors of this product should assure that adequate ventilation or other controls are used to control exposure. It is recommended that the current ACGIH-TLVs for thermal degradation by-products be observed.

### PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use

with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: Half- face filter respirator

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Eye Protection:** If contact is likely, safety glasses with side shields are recommended. If dusty conditions exist, chemical goggles are recommended.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

## ENVIRONMENTAL CONTROLS

See Sections 6, 7, 12, 13.

## SECTION 9

## PHYSICAL AND CHEMICAL PROPERTIES

Typical physical and chemical properties are given below. Consult the Supplier in Section 1 for additional data.

### GENERAL INFORMATION

Physical State: Solid  
Form: pellet  
Color: White  
Odor: Odorless  
Odor Threshold: N/D

### IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Softening point (C): 7 5 - 8 5  
Viscosity (cps@170 C): Max 20  
Density (g/cm<sup>3</sup> @25 C): 0.92±0.01  
Penetration @25C: Max 2 0

## SECTION 10

## STABILITY AND REACTIVITY

**STABILITY:** Material is stable under normal conditions.

**MATERIALS TO AVOID:** None

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**HAZARDOUS POLYMERIZATION:** Will not occur.

## SECTION 11

## TOXICOLOGICAL INFORMATION

### ACUTE TOXICITY

<b>Route of Exposure</b>	<b>Conclusion / Remarks</b>
<b>Inhalation</b>	
Toxicity: Data available.	Minimally Toxic . Based on test data for structurally similar materials .
Irritation: Data available.	Negligible hazard at ambient/ normal handling temperatures. Based on test data for structurally similar materials
<b>Ingestion</b>	
Toxicity: Data available.	Minimally Toxic . Based on test data for structurally similar materials .
<b>Skin</b>	
Toxicity: Data available	Minimally Toxic Based on test data for structurally similar materials
Irritation: Data available.	Negligible irritation to skin at ambient temperatures. Based on test data for structurally similar materials.

**CHRONIC/ OTHER EFFECTS****For the product itself:**

Elevated temperatures or mechanical action may form vapors, mists or fumes which may be irritating to the eyes and respiratory tract.

Additional information is available by request.

The following ingredients are cited on the lists below: None.

**--REGULATORY LISTS SEARCHED--**

1 = NTP CARC  
2 = NTP SUS

3 = IARC 1  
4 = IARC 2A

5 = IARC 2B  
6 = OSHA CARC

**SECTION 12****ECOLOGICAL INFORMATION**

The information given is based on data available for the material, the components of the material, and similar materials.

**ECOTOXICITY**

Material -- Not expected to be harmful to aquatic organisms.

Material -- Not expected to be harmful to terrestrial organisms.

**MOBILITY**

Material -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

**PERSISTENCE AND DEGRADABILITY****Biodegradation:**

Material -- Expected to be persistent .

**Hydrolysis:**

Material -- Transformation due to hydrolysis not expected to be significant .

**Photolysis:**

Material -- Transformation due to photolysis not expected to be significant .

**Atmospheric Oxidation:**

Material -- Transformation due to atmospheric oxidation not expected to be significant.

**BIOACCUMULATION POTENTIAL**

Material -- Potential to bioaccumulate is low.

**SECTION 13****DISPOSAL CONSIDERATIONS**

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

**DISPOSAL RECOMMENDATIONS**

Suitable routes of disposal are supervised incineration, preferentially with energy recovery, or appropriate recycling methods in accordance with applicable regulations and material characteristics at the time of disposal.

**REGULATORY DISPOSAL INFORMATION**

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

**SECTION 14****TRANSPORT INFORMATION**

**LAND (DOT) :** Not Regulated for Land Transport

**SEA (IMDG) :** Not Regulated for Sea Transport according to IMDG-Code

**AIR (IATA) :** Not Regulated for Air Transport

**SECTION 15****REGULATORY INFORMATION**

**OSHA HAZARD COMMUNICATION STANDARD:** When used for its intended purposes, this material is not classified as hazardous in accordance with OSHA 29 CFR 1910. 1200.

**NATIONAL CHEMICAL INVENTORY LISTING:** EINECS, TSCA

**EPCRA:** This material contains no extremely hazardous substances.

**CWA / OPA:** Plastic flake or powder are defined by the US EPA under the Clean Water Act (40CFR122.26) as a "significant material" which requires any industrial plant that may expose to storm water to secure a storm water permit. Violations of the rule carry the same penalties as other Clean Water Act violations. Powder & flake found in storm water runoff are subject to EPA regulations with the potential for substantial fines and penalties.

**SARA (311/312) REPORTABLE HAZARD CATEGORIES:** This product contains no extremely hazardous substances.

**SARA (313) TOXIC RELEASE INVENTORY:** This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

**The Following Ingredients are Cited on the Lists Below:** None.

**--REGULATORY LISTS SEARCHED--**

1 = ACGIH ALL	6 = TSCA 5a2	11 = CA P65 REPRO	16 = MN RTK
2 = ACGIH A1	7 = TSCA 5e	12 = CA RTK	17 = NJ RTK
3 = ACGIH A2	8 = TSCA 6	13 = IL RTK	18 = PA RTK
4 = OSHA Z	9 = TSCA 12b	14 = LA RTK	19 = RI RTK

5 = TSCA 4

10 = CA P65 CARC

15 = MI 293

Code key: CARC=Carcinogen; REPRO=Reproductive

**SECTION 16**

**OTHER INFORMATION**

N/D = Not determined, N/A = Not applicable

Document Group Number: SN/005/ 13

**THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**

No revision information is available.

-----  
**PRECAUTIONARY LABEL TEXT:**

Caution! Excessive exposure to dust may cause irritation of the nose and throat, and mechanical irritation of the eyes. Avoid generating dust. Use adequate ventilation under dusty conditions to keep airborne levels below recommended exposure limits. If inhaled and symptoms develop, remove to fresh air and get medical attention.

-----  
The information and recommendations contained herein are, to the best of FT wax's knowledge and belief, accurate and reliable as of the date issued. You can contact QINGDAO HONGSHENG to insure that this document is the most current available. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted.

-----  
The information supplied has been upon the current level of information available, for the purpose of specifying the requirements regarding environment, health and safety in conjunction with the product. They are not to be interpreted as a warranty for specific product characteristics. We take no responsibility for inappropriate use, processing and handling by purchasers and users of the product.